

FIBER BLOWING MACHINE MAH-4 ELEKTRONIK

The fiber blowing machine is equipped with:

- Equipment for blowing one fiber diameter (profiled pushing rollers blowing head insert)
- Fixings for three diameters of HDPE pipes
- User manual
- CE declaration
- Tool box
- A set of tools for operating the machine
- A pneumatic pistol for maintaining cleanliness
- Multifunctional intelligent controller with touch screen (two modes manual and automatic operation, full blowing report, recording of blowing parameters, reading weather conditions, GPS wireless connection and updates)
- Suitcase with battery and power cable
- Transport box
- Compressor with cooler and water separator required

Specification of fiber blowing machine

| | |
|---------------------------|---------------------------|
| Controller power supply | 12V (18AH battery) |
| Working pressure | 6-15 atmospheres |
| Engine operating pressure | 0.63 MPa |
| Head operating pressure | 6-15 atmospheres |
| Speed of input fibre | 0-100 m / min |
| Engine air consumption | 48 m ³ / h |
| Head air consumption | 3-11 m ³ / min |
| Weight of machine | 60 kg |
| Dimension | 810mm x 530mm x 480mm |
| Bearing numbers | 32 pieces |
| Rolls number | 8 pieces |
| HDPE pipe diameter | 4mm-50mm |
| Fiber cable diameter | 3 mm - 17 mm |

